

# ISTANT

SIMPRE PRESSED BRASS MANIFOLD  
WITH ISOLATING TAPS



## Components

- 1 Manifold
- 2 Knobs
- 3 Gaskets

## Material

UNI EN 12165 CW617N - DW

ABS

EPDM

## EN GENERAL CHARACTERISTICS

Outlets side threaded 24x19

Centre distance 36 mm

Knobs fitted with red and blue stickers indicating the various domestic terminals

## OPERATING CONDITIONS


Maximum working temperature: 100 °C.

Maximum working pressure: 10 bar.

Pressure drops: See diagram on Technical Attachments.

GP 2752  
ISTANT

Simple MODULAR manifold with isolating taps assembled together by bridging piece (art. 013072), made from pressed brass, for domestic hot water systems, nickel-plated, for copper, multilayer, PE-X, PP and PB pipes.



CODE	Model	A	B	C	D	E	F	Ch	Pack
		mm	mm	mm	mm	mm	mm	mm	pcs/box
9693R002	3/4" - 2 WAYS	3/4"	25	36	24,5	24x19	86	31	10
9693R003	3/4" - 3 WAYS	3/4"	25	36	24,5	24x19	122	31	6
9693R004	3/4" - 4 WAYS	3/4"	25	36	24,5	24x19	158	31	6
9694R002	1" - 2 WAYS	1"	27	36	27,5	24x19	92	37	8
9694R003	1" - 3 WAYS	1"	27	36	27,5	24x19	128	37	6
9694R004	1" - 4 WAYS	1"	27	36	27,5	24x19	164	37	4

GP 2799  
ISTANT

ISTANT manifold bridging piece, with O-ring.



CODE	Model	gr	Pack
			pcs/box
01307200	3/4"	22	10
01307210	1"	35	10